

Technická specifikace - Podložky ze sklotextilu

TYP: DE

T29 - zkosené

Průměr lamel.kotouče	Prům. podlož.	Díra H	Počet vrstev	Typ sklotextilu		Tloušťka podložky	Obv.ház. max.	Souosost max.	Úhel zkosení	Průměr K	Průměr L	Počet střed.vlož	Hmotnost podložky
				Počet vrstev									
∅	+/- 1,0 mm	+ 0,25/- 0,0 mm	ks	220 gr	260 gr	+/- 0,2 mm	mm	mm	+/- 1°	+ 3,0 / - 0,0 mm	+ 3,0 / - 0,0 mm	ks / se 6 záseky	gramů +/- 2,0
100	95,0	16,3	6	1	5	2,0	0,4	0,4	9°	35,0	55,0	1,0	22,0
			7	2	5	2,2	0,4	0,4	9°	35,0	55,0	1,0	24,0
			8	2	6	2,4	0,4	0,4	9°	35,0	55,0	1,0	26,0
115	105,0 - 108,0	22,23	5	1	4	2,5	0,4	0,6	9°	42,0	61,0	1,0	26,0
			6	2	4	2,6	0,4	0,6	9°	42,0	61,0	1,0	27,0
			7	1	6	2,8	0,6	0,6	9°	42,0	61,0	1,0	27,0
			8	2	6	2,9	0,6	0,6	9°	42,0	61,0	1,0	36,0
			9	2	7	3,2	0,6	0,6	9°	42,0	61,0	1,0	40,0
			10	2	8	3,4	0,6	0,6	9°	42,0	61,0	1,0	45,0
125	115,0 - 118,0	22,23	6	1	5	2,5	0,6	0,6	9°	42,0	61,0	1,0	30,0
			7	1	6	2,8	0,6	0,6	9°	42,0	61,0	1,0	31,0
			8	2	6	2,9	0,6	0,6	9°	42,0	61,0	1,0	44,0
			9	2	7	3,2	0,6	0,6	9°	42,0	61,0	1,0	49,0
			10	2	8	3,4	0,6	0,6	9°	42,0	61,0	1,0	55,0
150	141,0	22,23	7	1	6	3,0	0,8	0,8	8°/ 11°	52,0	87,0	1,0	53,0
			8	2	6	3,3	0,8	0,8	8°/ 11°	52,0	87,0	1,0	59,0
			9	2	7	3,4	0,8	0,8	8°/ 11°	52,0	87,0	1,0	65,0
180	170,0	22,23	7	1	6	3,0	1,0	1,0	8°/ 11°	52,0	87,0	1,0	67,0
			8	2	6	3,4	1,0	1,0	8°/ 11°	52,0	87,0	1,0	73,0
			9	2	7	3,7	1,0	1,0	8°/ 11°	52,0	87,0	1,0	75,0
			10	2	8	3,9	1,0	1,0	8°/ 11°	52,0	87,0	1,0	85,0

T27 - rovné

Průměr lamel.kotouče	Prům. podlož.	Díra H	Počet vrstev	Typ sklotextilu		Tloušťka podložky	Obv.ház. max.	Souosost max	Uhel zkosení	Průměr K	Průměr L	Počet střed.vlož	Hmotnost podložky
				Počet vrstev									
∅	+/- 1,0 mm	+ 0,25/- 0,0 mm	ks	220 gr	260 gr	+/- 0,2 mm	mm	mm	+/- 1°	+ 3,0 / - 0,0 mm	+ 3,0 / - 0,0 mm	ks / se 6 záseky	gramů +/- 2,0
100	95,0	16,3	6	1	5	2,0	0,4	0,4	0°	35,0	55,0	1,0	22,0
			7	2	5	2,2	0,4	0,4	0°	35,0	55,0	1,0	24,0
			8	2	6	2,4	0,4	0,4	0°	35,0	55,0	1,0	26,0
115	105,0 - 108,0	22,23	5	1	4	2,5	0,6	0,6	0°	42,0	62,0	1,0	26,0
			6	2	4	2,6	0,6	0,6	0°	42,0	62,0	1,0	27,0
			7	1	6	2,8	0,6	0,6	0°	42,0	62,0	1,0	27,0
			8	2	6	2,9	0,6	0,6	0°	42,0	62,0	1,0	36,0
			9	2	7	3,2	0,6	0,6	0°	42,0	62,0	1,0	40,0
10	2	8	3,4	0,6	0,6	0°	42,0	62,0	1,0	45,0			
125	115,0 - 118,0	22,23	6	1	5	2,5	0,6	0,6	0°	42,0	62,0	1,0	30,0
			7	1	6	2,8	0,6	0,6	0°	42,0	62,0	1,0	31,0
			8	2	6	2,9	0,6	0,6	0°	42,0	62,0	1,0	44,0
			9	2	7	3,2	0,6	0,6	0°	42,0	62,0	1,0	49,0
			10	2	8	3,4	0,6	0,6	0°	42,0	62,0	1,0	55,0
150	141,0	22,23	7	1	6	3,0	0,8	0,8	0°	50,0	82,0	1,0	53,0
			8	2	6	3,3	0,8	0,8	0°	50,0	82,0	1,0	59,0
			9	2	7	3,4	0,8	0,8	0°	50,0	82,0	1,0	65,0
180	170,0	22,23	7	1	6	3,0	1,0	1,0	0°	50,0	82,0	1,0	67,0
			8	2	6	3,4	1,0	1,0	0°	50,0	82,0	1,0	76,0
			9	2	7	3,7	1,0	1,0	0°	50,0	82,0	1,0	75,0
			10	2	8	3,9	1,0	1,0	0°	50,0	82,0	1,0	85,0

Na základě objednávky lze dodat také podložky ve tvaru T 28 - vypouklé, konvexní.